




DAVIEW MINI

DATASHEET

4
channels



Optional

- 01 • On/Off switch 02 • 1 COM port 03 • 4 USB 2.0 connections 04 • 1 stereo analog audio jack
- 05 • 1 slot for power cable 06 • 1 HDMI port 07 • 1 VGA port 08 • RJ45 network connector 10/100/1000
- 09 • 1 USB 2.0 connection 10 • 1 stereo analog audio jack 11 • 4 digital inputs 12 • 4 relays NA/NC

TECHNICAL SPECIFICATIONS

Processor	Intel
Memory (RAM)	4 GB
Hard drive	NAND flash memory based SSD (Solid State Drive)
Power supply	DC Power 12-19V, 65W (external power supply)
Power consumption	Approx. 30 W at full load
Power cord and plug	12v power supply and power cord
Environmental class	II (Indoor - General)
Housing	Ultra compact housing
Device dimensions in mm	135 x 35 x 128 mm (W x D x H)
Weight	630 gr
Communication protocols	TCP/IP, SMTP
Input and output ports	Input: 900, 5500, 21000 (customizable) Output: 9034, 465 (customizable)
Data protection	Digital signature

OPTIONAL

Input activation signal	USB external device, 4 N/C isolated inputs (dry contact)
Relay outputs	USB external device, 4 N/C relay outputs (dry contact), max. 6A at AC
Daview AMS	Alarm Management System for CMS with ClickThru™ technology

Intruder	Loitering
Vehicles	Appearance / disappearance
Entry / exit	Combination of rules
Tampering	



BARCELONA • SPAIN
+34 935 868 990

SANTIAGO DE CHILE • CHILE
+56 995 355 255

SINGAPORE
+65 9877 3532

MADRID • SPAIN
+34 918 294 186

BOGOTA • COLOMBIA
+57 3015389151

info@davantis.com
www.davantis.com

67 m
of detection

Range table for day/night cameras

	f (mm)	Height (m)	Sensor	HFOV (°)	Blind distance (m)	Distance (m)
Standard view	3	4	(1/3)"	77°	2	32
	8	4	(1/3)"	33°	8	67